

20-Series Micro-Chisel® BPX Saw Chains



.325" Power and performance meet enhanced kickback safety.

SPECIFICATIONS

Chain Pitch



Cutter Style

Micro-Chisel®

Kickback
Reduction



Recommended
Bar Length

11-20"
(28-50 cm)

Recommended
Saw Sizes

Gasoline-powered
2.3-3.8 cu. in.
(38-62 cc)

Recommended
User

Consumer



Commercial



Professional



Oregon® 20-series .325"-pitch saw chains are designed for chain saw users who desire performance coupled with low-vibration and enhanced kickback safety features.

FEATURES

BENEFITS

Advanced grind geometry

- Enhanced grind geometry significantly improves out-of-box sharpness with substantial speed improvement in boring and bias (undercut) modes.

Bumper drive link

- Reduces kickback without sacrificing performance
- Meets ANSI B175.1 standards for low-kickback saw chain

Blued cutters

- Provide superior corrosion resistance and improved strength

Micro-Chisel® cutters

- Small-radius working corners that are fast-cutting and easy to maintain



- Tie straps help keep oil where it's needed – on the chain.



- Oil holes in the drive links help carry oil around the full length of the guide bar groove.



- Chassis design increases operators' comfort level by reducing vibration at the handles.



- Top-plate witness mark makes accurate sharpening easier.

20-Series Micro-Chisel® BPX Saw Chains



SHARPENING NOTES

* When using an OREGON® file guide, ALWAYS hold it level, 0°, flat on the Top Plate



WARNING












This saw chain is low kickback chain. It met the reduced kickback requirements of ANSI B175.1 when tested on a representative sample of chain saws. Its safety features significantly reduce the hazard of kickback while maintaining high cutting performance.

ALL CUTTING CHAINS CAN KICK BACK, which may result in severe personal injury to the chain saw operator or bystanders. Operate your chain saw safely. Read all warnings in your chain saw operator's manual.








SHARPENING & GRINDING TOOL PART NUMBERS

						
	511AX 510A	31690	70503 (12)	5-3/4" Dia. OR 534-316	(12) 12211	(10) 31941

SHARPENING & GRINDING ANGLES


					
	3/16"	30°	10°		.025" / 0.6mm
					
	3/16"	30°	10°	55°	.025" / 0.6mm

SAW CHAIN REPLACEMENT PARTS AND NUMBERS



						
20BPX	P22574	P22575	P23843	P31939	P31940	P31938
21BPX	P22574	P22575	P23843	P31939	P34178	P34177
22BPX	P22574	P22575	P23843	P34185	P37530	P35711

Replacement parts come in packs of 25

CHAIN GAUGE

	20BPX	21BPX	22BPX
	.050"	.058"	.063"

OREGON® and Micro-Chisel® are registered trademarks and, Lubriwell, LubriLink, Vibe-Ban and Witness Mark are trademarks of Blount, Inc. For more information on these and other Oregon® products, contact your authorized Oregon® distributor, or:

 **OREGON®, BLOUNT, INC.** PO Box 22127 · Portland, OR, U.S.A. 97269-2127 Phone: 503-653-8881 Fax: 503-653-4201 Web: oregonchain.com
 **OREGON DISTRIBUTION LTD.** 505 Edinburgh Rd. N., Guelph, Ontario, Canada N1H 6L4 Phone: 519-822-6870 Fax: 519-822-4999